



ADHBLED1/ALU



Features

Decorative modern LED pendant c/w aluminium reflector

Suitable for industrial, commercial and retail applications

41W exceeds performance of 70W HQI

Matt grey textured powder coated finish

LED lifespan L70 54,000 hours

General Information

Lamp Type	LED
Colour / Finish	Matt Grey
IP Rating	IP20
Class Protection	1
Internal / External	Internal
Surface / Recessed / Suspended	Suspended
Warranty (Years)	5
CE Mark	Yes
Diameter (mm)	361
Height (mm)	430
Accessories	ADHBLED/PC/BC, ADHBLED/SK

Technical Information

Wattage	41W
Lumens Delivered	4760lm
Lm/W	114lm
Beam Angle	63
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20 to 25°C

Technical Data - ETIM - High bay luminaire (EC001716)

Mounting method	Pendant
With light source	Yes
Suitable for number of lamps	1
Material housing	Aluminium
Colour housing	Grey
Nominal voltage	230-230 V
Control gear included	Yes
No dim function	Yes
Light distributor	Reflector
Material reflector	Aluminium
Beam angle	Wide beam 41-80°
Degree of protection (IP)	IP20
Protection class	I
Max. system power	41 W
Rated luminous flux acc. IEC 62722-2-1	4760 lm
Colour of light	White
Colour temperature	4000-4000 K
Colour rendering index CRI	80-89
Height/depth	430 mm
Outer diameter	361 mm
Built-in width	205 mm

Datasheet generated from <https://onetimepim.com> last updated Tuesday, December 1, 2020 9:47:55 AM

