



ALUCLED/B/MWS/M3



Features

IP66 rated die-cast aluminium construction with tamper-proof stainless steel allen key screws to retain opal polycarbonate diffuser and frame.

One product with integral switches for multi-wattage and selectable CCT options.

18W exceeds performance of 38W TC-DD.

27W exceeds performance of 2x26W PL-C.

Powered by Tridonic

LED lifespan L70 60,000 hours.

Non-dimmable.

General Information

Lamp Type	LED
Colour / Finish	Black
Emergency	Yes
Integral Microwave Sensor	Yes
IP Rating	IP66
IK Rating	IK08
Class Protection	1
Internal / External	External
Surface / Recessed / Suspended	Surface
Warranty (Years)	5
CE Mark	Yes
Diameter (mm)	298
Depth (mm)	99

Technical Information

Wattage	18/27W
Lumens Delivered	1149/1622lm(Cool White, 18/27W), 1091/1563lm(Warm White, 18/27W)
Lm/W	64/60lm(Cool White, 18/27W), 61/58lm(Warm White, 18/27W)
CRI	Ra 80
CCT	3000/4000K
Input	220-240V
Hertz	50/60Hz
Operating Temp	-20°C to 25°C

Datasheet generated from <https://onetimepim.com> last updated Friday, March 26, 2021 11:29:11 AM

