DATASHEET




Code: 93SHSB

Cheriton Victorian | CHERITON VICTORIAN RANGE | Power Sockets


Product Image



Wiring



Dimensions



| Insert Type | Shaver Dual Voltage Unswitched Socket (Vertically Mounted) |
|----------------------------------|--|
| Insert Colour | Black |
| EAN13 Barcode | 5017503381036 |
| Commodity Code | 85363010 |
| Luckins TSI | 387387527 |
| ETIM Class | EC000186 |
| Dimensions(Nominal) | Double: Height = 146.0mm Width = 86.5mm Depth = 7.5mm |
| Weight | 809 GR |
| Fixing Hole Centres | Box Fixing = 120.6mm Grid Fixing = N/A |
| Minimum Wall Box Depth | 47mm |
| Switched Poles | None |
| Current Rating | 20VA |
| Voltage | 220/250V AC |
| Maximum Load | 200/250V input; 115/230V 20VA output |
| Mains Frequency | 50Hz |
| IP Rating | IP2XD |
| Contact Gap Minimum | None |
| Terminal Capacity 1 | 5 x1mm² |
| Terminal Capacity 2 | 4x1.5mm² |
| Terminal Capacity 3 | 3x2.5mm² |
| Terminal Capacity 4 | 2x4mm² Multi-strand |
| Terminal Capacity 5 | 1x6mm² |
| Earth Terminal Capacity 1 | 9x1mm² |
| Earth Terminal Capacity 2 | 6x1.5mm² |
| Earth Terminal Capacity 3 | 4x2.5mm² |
| Earth Terminal Capacity 4 | 2x4mm² Multi-strand |
| Earth Terminal Capacity 5 | 1x6mm² |
| Product Class 1 | Must be earthed |
| Ambient Operating Temperature | -5° to +40°C |
| Recommended Location | Internal Use Only |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | **W:** www.hamilton-litestat.com

(WEB

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 12/09/2023 ESOF.

DATASHEET



Code: 93SHSB

Cheriton Victorian | CHERITON VICTORIAN RANGE | Power Sockets

Maximum Installation Altitude 2000m

Standard/Approval BS EN 61558-2-5 + BS 4573

Additional Notes Must be mounted vertically. Shuttered: Yes. Box

Depth 47mm

Patents And Trade Marks Cheriton is a Registered Trade Mark No. 2344779