DATASHEET




Code: 93SS2AB-B

Cheriton Victorian | CHERITON VICTORIAN RANGE | Power Sockets


Product Image



Wiring



Dimensions



Insert Type	2 gang 13A Double Pole Switched Socket
Insert Colour	Antique Brass/Black
EAN13 Barcode	5017504018757
Commodity Code	85363010
Luckins TSI	387387611
ETIM Class	EC000125
Dimensions(Nominal)	Double: Height = 86.5mm Width = 146.0mm Depth = 7.5mm
Weight	280 GR
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = N/A
Minimum Wall Box Depth	35mm
Switched Poles	Double
Current Rating	13 Amp
Voltage	220/250V AC
Maximum Load	13 Amp
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	3mm
Terminal Capacity 1	4x2.5mm²
Terminal Capacity 2	3x4mm²
Terminal Capacity 3	2x6mm² Multi-Strand
Terminal Capacity 4	1x10mm²
Earth Terminal Capacity 1	4x2.5mm²
Earth Terminal Capacity 2	3x4mm²
Earth Terminal Capacity 3	2x6mm² Multi-Strand
Earth Terminal Capacity 4	1x10mm²
Product Class 1	Must be earthed
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	BS 1363-2

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | **W:** www.hamilton-litestat.com

(WER)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 07/09/2023 ESOF.

DATASHEET



Code: 93SS2AB-B

Cheriton Victorian | CHERITON VICTORIAN RANGE | Power Sockets

Additional Notes Dual Earth: Yes

Patents And Trade Marks Cheriton is a Registered Trade Mark No. 2344779