

PDFMMINIL

360° Flush Mount Linkable Mini PIR Sensor

Features & Benefits

- Designed For Corridor and Multi-Zone Use
- Mini unobtrusive design
- 360° Detection
- Twist & Lock Design For Easy Access
- Up To 5 Slaves Can Be Added To 1 Master. Pre-Wired RJ11 Plug-in Slave Units For Quick Installation
- LUX Adjustment
- Time Adjustment For Slave Units Set Via Master Only
- Termination Box For Ease Of Wiring
- Masking Kit Included
- LED movement indicator



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Flush Mount
Earth Class Rating	Class II (Power Box), Class III (PIRs)
Operating Temperature	-20°C to 40°C
Ingress Protection Rating	IP40
Setting Type	Dial
Approved Mounting Height (m)	2.5
Presence Detection (m)	3 Diameter
Motion Detection (m)	8 Diameter

Data sheet

PDFMMINIL

Light / PIR Presence Detectors

Detection Angle	360°
Hole Cut-Out Size (mm)	40
Standby Consumption	<0.5W
Number of Channels	1
Switch rating	250W LED/CFL/Fluorescent, 2300W Halogen
ON Time Adjustment	30 Sec, 2m, 5m, 10m, 15m, 30m. User Adjustable
Lux Level	10 to 2000
Detection Range (M)	8 Diameter
Permanent ON Facility	Yes (Pulse Override)
Dusk Till Dawn	No
Multiple Unit Support	Up to 5 PDFMMINILS (Slave PIRs)
Cable Entry(s)	Side Entry (Power Box)

General

Weight (g)	140
Height (mm)	PIR 47, Power Box 35
Width (mm)	PIR 47, Power Box 175
Depth (mm)	PIR 64, Power Box 35
Body Construction	Polycarbonate
Product Colour	White
Accessories (Optional)	PDFMINILS (Slave PIR)
EAN Number	5012483014011
Guarantee Period	3 Years
Trade Tariff Commodity Code	8536508090

Line Diagrams

