



APRILEDP/CCT



Features

220-240V IP65 dimmable LED 4 CCT selectable fire rated performance downlight suitable for residential and hospitality applications

Remote driver with 2x1.5mm² + CPC loop-in, loop-out colour coded push fit piano terminals provide an easy and efficient installation

Matt bezel supplied as standard. Chrome, satin chrome and matt black bezels available to purchase separately

Detachable LED driver for fast fix install

Low profile design and remote driver allows installation into shallow ceiling voids

Fully tested for 30, 60 and 90 minute ceiling types to meet Part B of building regulations

Fully tested to meet Part C (moisture), Part E (acoustic) and Part L (energy) of Building Regulations

Wide 60° beam angle for increased light distribution

General Information

Lamp Type	LED
Dimmable	Yes
Fire Rated	Yes
IP Rating	IP65
Class Protection	1
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lifetime (Hrs)	L70 60,000
Warranty (Years)	5
CE Mark	Yes
Diameter (mm)	90
Height (mm)	55
Accessories	APRILEDPBZ/CH, APRILEDPBZ/SC, APRILEDPBZ/BLK, ACFLP/3, APRILEDP/CP/MW, APRILEDP/CP/CH, APRILEDP/CP/SC, APRILEDP/CP/BLK

Technical Information

Wattage	7W
Lumens Delivered	610lm (4000K)
Lm/W	87lm (4000K)
Beam Angle	60
CRI	Ra 80
CCT	2700K/3000K/4000K/6000K
Input	230V
Hertz	50/60Hz
Operating Temp	-5°C to 25°C
SDCM	6
UGR	23

Datasheet generated from <https://onetimepim.com> last updated Tuesday, April 26, 2022 10:27:46 AM

