



## ATSLED/3NM/ST/HO



## Features

Self-test Twin LED emergency floodlight for industrial applications

Exceeds performance of 2x20W halogen equivalent

Robust white moulded enclosure

Moulded polycarbonate heads

Self-test as standard

## General Information

|                                |                   |
|--------------------------------|-------------------|
| Lamp Type                      | LED               |
| Colour / Finish                | White             |
| Self Test                      | Yes               |
| IP Rating                      | IP66              |
| Class Protection               | 1                 |
| Internal / External            | Internal/External |
| Surface / Recessed / Suspended | Surface           |
| Warranty (Years)               | 5                 |
| CE Mark                        | Yes               |
| Width (mm)                     | 300               |
| Height (mm)                    | 290               |
| Depth (mm)                     | 70                |
| Accessories                    | ASBP/6/LI         |

## Technical Information

|                  |                   |
|------------------|-------------------|
| Wattage          | 3.3W              |
| Lumens Delivered | 670lm (Emergency) |
| CCT              | 6500K             |
| Input            | 220V-240V         |
| Hertz            | 50Hz              |
| Operating Temp   | 5C° to 40C°       |

## Technical Data - ETIM - Emergency luminaire (EC001957)

|                           |                      |
|---------------------------|----------------------|
| Mounting method           | Wall surface mounted |
| Monitoring equipment      | Automatic self test  |
| With light source         | Yes                  |
| Number of lighting heads  | 2                    |
| Material housing          | Plastic              |
| Colour housing            | White                |
| Nominal voltage           | 220-240 V            |
| Degree of protection (IP) | IP66                 |
| Protection class          | I                    |
| Max. system power         | 3.3 W                |
| Colour temperature        | 6500-6500 K          |
| Width                     | 300 mm               |
| Height/depth              | 70 mm                |
| Length                    | 290 mm               |

Datasheet generated from <https://onetimepim.com> last updated Friday, October 15, 2021 11:24:49 AM

