



AWO50



Features

Supplied with both MR16 and GU10 lampholders.

Compact inground uplight which accepts 12V and mains halogen, CFL and LED lamps.

Housing in die-cast aluminium with clear toughened glass diffuser of 10mm thickness.

316 stainless steel top ring and stainless steel allen key screws.

Suitable for light vehicular traffic with a static impact resistance of up to 2000kgs.

Supplied with recessed sleeve in high resistant thermoplastic.

General Information

Lamp Type	MR16 / GU10
Colour / Finish	Stainless Steel
OCTO Compatibility	Smart Outdoor controller
IP Rating	IP67
Class Protection	1, 3
Internal / External	External
Surface / Recessed / Suspended	Recessed
Warranty (Years)	3
CE Mark	Yes
Diameter (mm)	98
Depth (mm)	155

Technical Information

Wattage	50W
---------	-----

Technical Data - ETIM - In-ground luminaire (EC000758)

Lamp type	Other
With light source	No
Suitable for number of lamps	1
Colour housing	Stainless steel
Material cover	Glass transparent
Degree of protection (IP)	IP67
Max. system power	50 W
Height/depth	155 mm
Outer diameter	98 mm
Max. load	2000 kg
Over rollable	Yes

Datasheet generated from <https://onetimepim.com> last updated Monday, September 6, 2021 12:41:35 PM

