

ECLIPSE LED

The Eclipse is a popular and efficient alternative to louvred or conventional flat panel technology for concealed fix ceilings. This attractive luminaire creates a subtle lighting effect.

FEATURES

- Luminaire suitable for 15mm and 24mm exposed T grid system
- Manufactured from mild steel
- Constant output driver
- Range of sizes and outputs



LED

IP20

T5
EQUIVALENT

5 YEAR
WARRANTY

TECHNICAL DETAILS

Part Number	Description	Replaces	Weight (kg)	No. Per 10A Breaker	Inrush Current (A)	Circuit Watts	Board Lumens	Luminaire Lumens	LI/cw
ECE-20-55-4K	20W 495 x 495 LED Luminaire	2 x 36W PL	2.9	50	5A 37μs	27	3352	2447	122.3
ECE-20-4K-HE	20W 595 x 595 LED Luminaire	4 x 14W T5	3.3	50	5A 37μs	20	3352	2447	122.3
ECE-27-4K-HE	27W 595 x 595 LED Luminaire	4 x 24W T5	5.9	50	5A 37μs	27	4525	3303	122.3
ECE-54-4K-HE	54W 1195 x 595 LED Luminaire	4 x 54W T5	6.3	20	12A 50μs	54	9049	6606	122.3

OPTIONS AND ACCESSORIES

EM	Integral Emergency (1W)
EMST	Integral Emergency Self Test (1W)
CF	Corridor Function
MWP	Remote Programmable Microwave
WL	Wireless Control System
WLEM	Wireless Emergency Monitoring
DD	SwitchDIM/DALI
3K	3000K Colour Temperature
5K	5000K Colour Temperature

PHOTOMETRIC AND DIMENSION

