



01604 495 151
collingwoodlighting.com

 collingwoodled

 /collingwoodlighting

 collingwoodlighting

GL050

3W, 50lm marker ground light

Features

IK rating	IK08
IP rating	IP68
Colour flexibility	Fixed colour
Walk Over / Drive Over	Walk over
Input	350mA
LED Lifetime	70,000h L70
CRI	>80Ra or -
SDCM	3SDCM

Installation information

Cut Out Size	Ø 70mm
Bathroom zone	0
Construction Material	Stainless steel (316)
Weight	552g
Maximum ambient temperature	35°C
Electric Class (1, 2, 3)	3

Guarantee

7 year extended warranty

Features & benefits

3W at 350mA

Frosted effect for low glare and soft lighting

Low voltage groundlight

Robust cable for outdoor use

Brushed steel finish for sleek effect

Photometrics @ 25°C

Product code	W	Colour	Beam	lm	lm/W	lx @ 1m
GL050 NW	3W	4000K	100°	50	17	20
GL050 WW	3W	3000K	100°	46	15	16
GL050 27	3W	2700K	100°	46	15	16
GL050 BLUE	3W	Blue	100°	7	2	2

Wiring information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED drivers

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	3
PLR/350 1-5	N/A	Yes	No	0	1	1
PLD UNI-DRIVE 350MA	N/A	Yes	Yes (1-10V)	2	1	3

Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors
TUBE/68	Installation tube
WCR 275 BLACK	2-core rubber cable
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types

