

GALE LED



Surface mounted corridor or classroom fitting with low UGR rating. Polycarbonate diffuser and screw retained end caps for security.

FEATURES

- Surface LED fitting
- Polycarbonate diffuser
- Screw retained end caps for security
- 3K, 4K & 5K colour options
- Completely flush ceiling mounted luminaire



LED

IP44

T5/T8
EQUIVALENT

5 YEAR
WARRANTY

TECHNICAL DETAILS

Part Number	Description	Replaces	Weight (kg)	No. Per 10A Breaker	Inrush Current (A)	Circuit Watts (W)	Board Lumens	Luminaire Lumens	LI/cW
GALE-32-LED-4K-HE	32W 1200mm Surface Luminaire	2 x 36W T8	2.8	50	5A 37μs	32	5550	3885	121.4
GALE-44-LED-4K-HE	44W 1200mm Surface Luminaire	2 x 54W T5	2.8	35	5A 37μs	44	7631	5342	121.4
GALE-38-LED-4K-HE	38W 1500mm Surface Luminaire	2 x 35W T5	3.4	35	5A 37μs	38	6590	4613	121.4
GALE-53-LED-4K-HE	53W 1500mm Surface Luminaire	2 x 58W T8	3.4	35	12A 50μs	53	9192	6434	121.4
GALE-48-LED-4K-HE	48W 1800mm Surface Luminaire	1 x 70W T8	4.08	35	12A 50μs	48	8325	5827	121.4
GALE-68-LED-4K-HE	68W 1800mm Surface Luminaire	2 x 70W T8	4.08	25	15A 50μs	68	11793	8255	121.4

OPTIONS AND ACCESSORIES

EM	Integral Emergency (1W)
EMST	Integral Emergency Self Test (1W)
CF	Corridor Function
MWP	Remote Programmable Microwave
WL	Wireless Control System
WLEM	Wireless Emergency Monitoring
DD	SwitchDIM/DALI
3K	3000K Colour Temperature
5K	5000K Colour Temperature

PHOTOMETRIC AND DIMENSION

