

LED LIGHTPACK - CLP

The LED lightpack is an energy saving lighting concept, which can be fitted with a variety of sensors for further savings. Fitted with SELV: Safe Extra Low Voltage for your safety. With easy to detach end caps and diffuser for easy installation.

FEATURES

- Manufactured from mild steel
- Specially designed acrylic diffuser
- Constant output driver
- Range of outputs and sizes



LED

IP20

T8
EQUIVALENT

5 YEAR
WARRANTY

TECHNICAL DETAILS

Part Number	Description	Replaces	Weight (kg)	No. Per 10A Breaker	Inrush Current (A)	Circuit Watts (W)	Board Lumens	Luminaire Lumens	LI/cW
CLP-2-CO-4K	2FT Single CLP Lightpack	1 x 18W T8	1.1	25	12.5A 180µs	11	1,778	1,408	128
CLP-3-CO-4K	3FT Single CLP Lightpack	1 x 18W T8	1.5	25	12.5A 180µs	11	1,778	1,408	128
CLP-4-CO-4K	4FT Single CLP Lightpack	1 X 36W T8	1.9	25	12.5A 180µs	22	3,556	2,816	128
CLP-5-CO-4K	5FT Single CLP Lightpack	1 X 58W T8	2.5	25	12.5A 180µs	27	4,364	3,456	128
CLP-6-CO-4K	6FT Single CLP Lightpack	1 X 70W T8	2.9	25	12.5A 180µs	33	5,333	4,224	128
CLP-2T-CO-4K	2FT Twin CLP Lightpack	2 x 18W T8	1.1	25	12.5A 180µs	23	3,717	2,944	128
CLP-3T-CO-4K	3FT Twin CLP Lightpack	2 x 18W T8	1.5	25	12.5A 180µs	23	3,717	2,944	128
CLP-4T-CO-4K	4FT Twin CLP Lightpack	2 X 36W T8	2.0	25	12.5A 180µs	47	7,596	6,016	128
CLP-5T-CO-4K	5FT Twin CLP Lightpack	2 X 58W T8	2.4	25	12.5A 180µs	53	8,566	6,784	128
CLP-6T-CO-4K	6FT Twin CLP Lightpack	2 X 70W T8	3.0	25	15A 180µs	70	11,313	8,960	128

OPTIONS AND ACCESSORIES

EM	Integral Emergency (1W)
EMST	Integral Emergency Self Test (1W)
DD	SwitchDIM/DALI
MWP	Remote Programmable Microwave
5K	5000K Colour Temperature

PHOTOMETRIC AND DIMENSION

