

Technical Specification



Product Code: MM038WH Description: 5A Round Pin Socket Outlet Module





Terminals: Brass

Terminal Torque Value (Nm) 1.2

General Information

Dimensions (mm) 50 (W) x 50 (H) x 27.1 (D)

Finish Polar White

Materials Cover & Housing: Polycarbonate

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Frequency (Hz) 50

Anti Microbial Certified No

Rated Voltage (V~) (Ue) 250

Resistive Load Rating (A) 5

Termination Type Screw

Terminal Size (mm) Ø5

1) Ø5

Terminal Capacity - Solid (mm²) 4 x 1.5 or 3 x 2.5 Minimum Back Box Depth (mm) 25 (35 Flat Plate)

Willimum back box Depth (IIIII) 25 (35 Flat F

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS 546

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.