

MUNICIPAL LED

With its curved profile and dust limiting, wipe clean diffuser, the LED Municipal has been designed as a contemporary and attractive solution for education and healthcare establishments.

FEATURES

- PMMA wipe clean smooth diffuser
- Manufactured from mild steel
- Available with night light function
- Screw fixed polycarbonate end cap



LED

IP44

T5
EQUIVALENT

5 YEAR
WARRANTY

TECHNICAL DETAILS

Part Number	Description	Replaces	Weight (kg)	No. Per 10A Breaker	Inrush Current (A)	Circuit Watts (W)	Board Lumens	Luminaire Lumens	LI/cW
MUN 22-2T-CO-4K	630mm 22W Luminaire	2 x 18W T8	2.2	50	5A 37μs	22	3815	2722	123.7
MUN 22-3-CO-4K	1030mm 22W Luminaire	2 x 30W T8	3.3	50	5A 37μs	22	3815	2722	123.7
MUN 32-4-CO-4K	1230mm 32W Luminaire	2 x 36W T8	3.9	50	5A 37μs	32	5550	3885	121.4
MUN 44-4T-CO-4K	1230mm 44W Luminaire	2 x 54W T5	3.9	35	5A 37μs	44	7631	5444	123.7
MUN 38-5-CO-4K	1530mm 38W Luminaire	2 x 35W T5	5.2	35	5A 37μs	38	6590	4613	121.4
MUN 53-5T-CO-4K	1530mm 53W Luminaire	2 x 58W T8	5.2	35	12A 50μs	53	9192	6434	121.4
MUN 48-6-CO-4K	1830mm 48W Luminaire	1 x 70W T8	6.3	35	12A 50μs	48	8325	5827	121.4
MUN 68-6T-CO-4K	1830mm 68W Luminaire	2 x 70W T8	6.3	25	15A 50μs	68	11793	8166	120.1

OPTIONS AND ACCESSORIES

EM	Integral Emergency (1W)
EMST	Integral Emergency Self Test (1W)
CF	Corridor Function
MWP	Remote Programmable Microwave
CMK	Corner Mounting Kit
NL	Integral 3W Night Light
WL	Wireless Control System
WLEM	Wireless Emergency Monitoring
DD	SwitchDIM/DALI
3K	3000K Colour Temperature
5K	5000K Colour Temperature

PHOTOMETRIC AND DIMENSION

