



INCEPTOR® B-LITE

Technical Specification

Product Code: OV82180

Description: 50-70W 1800mm Multi-Current Linear LED Batten



General Information

Dimensions (mm)	1800 (L) x 63 (W) x 80 (D)
Materials	Base: Powdercoated Steel; Opaque Diffuser: Polycarbonate
Base Finish	White (RAL 9003)
Product Weight (Kg)	1.9
Ingress Protection	IP20
Impact Rating (IK)	08
Mounting	Ceiling or Wall
Warranty (Years)	5

Supply & Power Information


Input Voltage & Frequency (V~ / Hz)	200-240 50
Safety Class	I
Surge Protection Installed	
Circuit Wattage (W)	50/58/64/70
Input Current (A)	360
Inrush Current	0.36A (<0.5S)
Power Factor	>0.9
Operating Temperature (°C)	-20 to +45
Maximum Critical Temperature (°C)	+80
Input Terminations	3 Pole Push Fit Terminals

Luminaire Output


LED Wattage	50	58	64	70
Typical Luminous Flux	5250	6090	6720	7350
Efficacy	105	105	105	105
Circuit Wattage	50	58	64	70
Beam Angle (°)	120			
Colour Temperature (K)	4000			
Flicker Free	Yes			
Colour Rendering Index (CRI)	>80			
Energy Classification	F			
LED Lifetime (L70)	50000			

Dimming Information


Dimmable	No
----------	----




50W



58W



64W



70W



OVIA Limited, Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom

T: +44 (0)1827 300640

E: sales@oviaUK.com | W: oviaUK.com



DoC



Installation

