


INCEPTOR® HI-LITE

Technical Specification

Product Code: OXHL100

Description: 100W LED 0(1)-10V Dimmable Highbay IP65 CTA Black



General Information

Dimensions (mm)	262 (Dia.) x 104 (D)
Materials	Body: Powdercoated Aluminium; Diffuser: Polycarbonate
Finish	Black (RAL 9005)
Product Weight (Kg)	2.1
Ingress Protection	IP65
Impact Rating (IK)	10
Fixing Components Supplied	Suspension Point Within Moulding
Warranty (Years)	6

Supply & Power Information

Input Voltage & Frequency (V~ / Hz)	220-240 50/60
Safety Class	I
Circuit Wattage (W)	100
LED Wattage (W)	100
Input Current (mA)	361-1000
Inrush Current	75A (288µs)
Power Factor	>0.9
Operating Temperature (°C)	-40 to +50
Minimum Critical Temperature (°C)	-40
Maximum Critical Temperature (°C)	+90
Input Mains Cable	3 x 1mm² H05RN-F (3 Metres)
Analogue Input Cable 0(1)-10V	2 x 20 AWG (3 Metres) - Black

Luminaire Output

Colour Temperature (K)	4000	5000	6500
Typical Luminous Flux (lm)	15500	16500	15000
Efficacy (lm/W)	155	165	150
Beam Angle (°)	90		
Colour Rendering Index (CRI)	80		
Flicker Free	Yes		
Energy Classification	D		
LED Lifetime (L70) (Hours)	50000		

Dimming Information


Dimmable	Yes
Dimming Format	0(1)-10V

Compatible Accessories

OWWB1080 - 270mm Bracket For Highbay Fitting
OHLEMP - 5W 3 Hour Maintained IP65 Emergency Pack
OEPCL05 - Highbay Emergency Pack Coupler Lead 0.5M
OEPCL1 - Highbay Emergency Pack Coupler Lead 1M
OVHBDACV - IP67 DALI To PWM Signal Convertor

Additional Information

Shorting cap supplied which is removable for emergency pack installation



Ovia Limited, Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom

T: +44 (0)1827 300640

E: sales@oviaUK.com | W: oviaUK.com

