

**PERFORMANCE PLUS CIRCULAR HIGH BAY 1PK IP65 20250LM 150W 4000K
120 BEAM INTEGRAL 1-10V DIM**

ILHBC217



Bright, efficient and adaptable, the Perform+ Circular High Bay offers a range of options for bringing bright light to large indoor facilities, while reducing glare with its range of diffuser and reflector accessories. All models are rated IP65 and run at 135lm/W.

Details

Quick Order Code:	381440
Barcode:	5055788239536
Category:	Luminaires
Range Name:	Perform+
Product Body Finish:	Matt Black
Market Segment:	Commercial indoor, Industrial indoor
Finish:	Matt Black
Warranty (Years):	5
CE RoHS:	Yes

Physical Data

Product Length (mm):	137.5
Product Weight (g):	3200
Optic:	Polycarbonate diffuser
Material:	Aluminium, Polycarbonate
Overall diameter (mm):	280
Construction:	Aluminium heat-sink, PC injection moulded driver case
Bulb or Luminaire Shape:	Round
Luminaire Fixing:	Suspended
Placement / Application:	Indoor, Outdoor, General Lighting

Electrical Data

Power Consumption (w):	150
Power Factor:	0.9
Wattage equivalent (W):	450
Dimming:	Dimmable
Driver Included:	Yes
Electric Current:	AC



EN:	EN-60598, EN61000, EN61547, EN55015, IEC62321
LVD Certified:	Yes

Light Data

Luminous Flux in Lumens (lm):	20250
Luminous efficacy (lm/W):	135
Correlated Colour Temperature (CCT) (K):	4000
Colour Temperature:	4000K - Cool White
Colour Temperature Name:	Cool White
Beam Angle:	120
Colour Rendering Index (CRI):	80
Frequency Range (Hz):	50/60
Instant on (Less than 1 second):	Yes
LED Size (mm):	3030
LED Type:	Surface mounted device (SMD)
Lifetime (hours):	100000
Switching Cycles:	20000
Useful Lumens (lm):	400

Environment

EN:	EN-60598, EN61000, EN61547, EN55015, IEC62321
LVD Certified:	Yes
CE RoHS:	Yes
New Energy Rating:	D
EU Luminaire:	L
Hg 0% (Mercury Free):	Yes
IK Rating (Impact Protection):	IK08
IP Rating (Ingress Protection):	IP65
Lowest Operating Temperature (°C):	-40
Maximum Operating Temperature (°C):	50



Packaging

Package Weight (g):	3490	Portal.integral-led.com
Package Length (mm):	330	

Product Design And Specification Subject To Change Or Modification Without Notice. Image For Illustration Only. E&OE

Package Width (mm):	330
Package Depth (mm):	205