

**TITLE:**

USC2 1pr Unscreened LSZH

CODE:

SFX/USC2-14-LSZH-GRY-1

DESCRIPTION:

1m (per metre) USC2-14 1pr
14AWG Unscreened 600V Grey
LSZH (8473)

SUPPLIED AS:

Per 1m Lengths

- General purpose single paired cables
- Small overall diameter and used in applications such as security, audio and instrumentation
- Low smoke zero halogen plastic is good for use inside public buildings and spaces as will not emit toxic gases if the cable catches fire
- Improved performance and protection against fire



enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23



Product Specification



Cable Construction

Cable Construction	2 Cores
CPR	Eca
Conductor	Tinned Copper
Conductor Diameter (mm)	0.3 ±0.008 x 42(2.08mm²)
Stranded Diameter (mm)	2.00
Overall Diameter (mm)	9.00 ±0.20

Insulation

Insulation	LSZH
Insulation Colour	Black, White
Insulation Resistance @20°C	>200MO/km
Insulation Thickness (mm)	0.80

Outer/Jacket Specification

Jacket	LSZH
Overall Colour	Grey
Overall Diameter (mm)	9.00 ±0.20
Jacket Colour	Grey RAL 7042
Jacket Thickness (mm)	1.00 ±0.20

Electrical Characteristics

Insulation Resistance @20°C	>200MO/km
Max Conductor DC resistance @ 20°C	9.50O/km
Rated Temperature (°C)	-40°C to 70°C
Rated Voltage (V)	600V





BELDEN CABLE



CONSTRUCTION PRODUCTS REGULATIONS:

Sorry, No CPR information is available for this product

Belden Cable



enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23

TERMS AND CONDITIONS APPLY - WHILE EVERY EFFORT HAS BEEN MADE TO ENSURE THE ACCURACY AND COMPLETENESS OF THE INFORMATION, NO GUARANTEE IS GIVEN NOR RESPONSIBILITY TAKEN FOR ERRORS OR OMISSIONS IN THIS DATA SHEET.

