



## DATASHEET



### BATCA6H

230V 6ft 67W LED CCT Batten High Lumen

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)



| MLA PART CODE                 | BATCA6H                                                          |
|-------------------------------|------------------------------------------------------------------|
| DESCRIPTION                   | 230V 6ft 67W LED CCT Batten High Lumen                           |
| NET WEIGHT (KG)               | 1.9                                                              |
| FINISH                        | White                                                            |
| DIFFUSER                      | Opal                                                             |
| DIMENSIONS (MM)               | Length - 1734<br>Height - 61<br>Width - 71                       |
| CONSTRUCTION                  | Construction - Pressed steel<br>Construction 2 - & polycarbonate |
| CLASS                         | I                                                                |
| IP RATING                     | IP20                                                             |
| WATTAGE (W)                   | 67                                                               |
| LAMP TECHNOLOGY               | SMD LED                                                          |
| LAMP INCLUDED                 | Yes                                                              |
| LUMENS (LM)                   | 7960/8535/7805                                                   |
| LUMENS LIGHT SOURCE ONLY (LM) | 9395                                                             |
| LUMEN TOLERANCE               | 5%                                                               |
| EFFICACY (LM/W)               | 138.9                                                            |
| CIRCUIT WATTAGE (W)           | 61.4                                                             |
| CCT                           | 3000/4000/6000K                                                  |
| LIGHT COLOUR                  | CCT                                                              |
| CRI                           | >85                                                              |
| SDCM                          | <6                                                               |
| RUNNING CURRENT (A)           | 0.28                                                             |
| DISPLACEMENT FACTOR           | >0.7                                                             |
| SVM                           | 0.004                                                            |
| PST-LM                        | 0.037                                                            |
| BEAM ANGLE (DEGREES)          | 140                                                              |
| L70B50 LIFESPAN (HRS)         | 50,000                                                           |

|                                          |                                                                                                                                                                                                     |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DIMMABLE                                 | No                                                                                                                                                                                                  |
| OPERATING TEMPERATURE                    | -20~45°C                                                                                                                                                                                            |
| INPUT VOLTAGE                            | 230V 50Hz                                                                                                                                                                                           |
| CABLE GLAND INCLUDED                     | Open grommet                                                                                                                                                                                        |
| DRIVER                                   | DRIVER TYPE - Constant Current<br>MAX. OUTPUT - 60W<br>OUTPUT VOLTAGE - 28-40V<br>OUTPUT CURRENT - 1500mA<br>POWER FACTOR - 0.95<br>AMBIENT TEMPERATURE (Ta) - 60°C<br>CASE TEMPERATURE (Tc) - 90°C |
| WARRANTY                                 | 5year(s)                                                                                                                                                                                            |
| ORIGIN OF MANUFACTURE                    | China                                                                                                                                                                                               |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes                                                                                                                                                                                                 |
| EAN                                      | 5056270886405                                                                                                                                                                                       |

Date Created: 21/10/2022 10:12

